

<b>FORM</b> Identifier: F 108 Revision: 04 Page: 1/1	<b>Product specification          for inductive components</b>	<b>MAGNETEC GmbH</b> Industriestrasse 7 D-63505 Langenselbold
---	--	---



<b>Client:</b>	<b>MAGNETEC</b>	<b>Magnetec P/N:</b>	<b>M-046</b>	<b>Magnetec A/N:</b>	<b>12052</b>
<b>Client's P/N:</b>	/	<b>PS Index:</b>	<b>02</b>	<b>PS Revision:</b>	<b>03</b>
<b>Subject:</b>	<b>EMC Wandler</b>			<b>Type:</b>	<b>E</b>

<b>1. Mechanical Outline</b> Nominal core dimensions: <b>31,5 x 20 x 15</b> Finished product dimensions: OD ≤ 32,9 ID ≥ 18,5 H ≤ 17,2 [dimensions] = mm		
--	--	--

<b>2. Core data (nominal values)</b>			
Core material:	<b>NANOPERM®</b>	$L_{Fe} = 7,95 \text{ cm}$	$A_{Fe} = 0,67 \text{ cm}^2$
Permeability level:	<b>90 000</b>	@ frequency <b>10 kHz</b>	@ H peak <b>3,6 mA/cm</b>

<b>3. Inspection values</b>				
	Measured value	Measurement limits	Frequency	leff x N [mA x turn]
	AL [μH]	66 - 132	10 kHz	20
	AL [μH]	15,7 - NA	100 kHz	20

<b>4. Core finishing</b>	
Type:	<b>Epoxy coated</b>
Marking:	<b>MAGNETEC M-046-02 YM (YM = Year/Month), acc. to IEC 60062 6.1.1</b>
Packaging:	<b>35 pcs. per layer; 5 layers per carton box ; PU = 175 pcs.</b>

<b>5. Comments:</b>	

Index / Revision	Alteration	Date
01/ 01	Product Specification	25.10.2000
01/ 02	New format / PU = 175 pcs.	28.11.2007
02 / 03	Nominal permeability given and 10kHz upper and 100kHz lower limit defined	18.06.2014

<b>Created:</b>	Z. Palánki	<b>Approved (Techn):</b>	F. Zámorszky	<b>Approved (Quality):</b>	J. Gulyás	<b>Released:</b>	T. Trupp
	18.06.2014		27.06.2014		27.06.2014		27.06.2014