

Product specification for inductive components

CONFIDENTIAL - Reproduction, publication and dissemination of this publication, enclosures hereto and the information contained therein is prohibited without MAGNETEC 's prior written consent.

Client:	MAGNETEC	Magnetec P/N:	M-1053		
Client's P/N:	/	PS Index:	01	PS Revision:	01
Subject:	EMC Wandler				

1 Machanian Quilling							
1. Mechanical Outline Nominal equivalent round							
core:		Marking					
80 x 63 x 30							
Finished product dimensions: OD ≤ 85 ID ≥ 57 H ≤ 35,5 [dimensions] = mm				Н			
2. Core data (nominal values Core material: Permeability level :) NANOP 12 000	@ frequency	A _{Fe} = 1,86 cm ² @ H peak 3 mA/cm				
3. Inspection values (at room	tempera	ture, unless otherwise stated)					
Measured value		Measurement limits	Frequency	leff x N [mA x turn]			
AL [µH]		8,9 - 17,8	10 kHz	47			
AL [µH]		6,6 - NA	100 kHz	47			
4. Core finishing							
		1 YM (YM = Year/Month), acc. to rers per carton box; PU = 12 pcs.					
5. Comments							
Visit <u>http://www.magnetec</u> .	.de/filead	min/pdf/pb_ds.pdf for further info	ormation.				
Index / RevisionAlteration01 / 01First issue				Date 20.06.2016			
Created: Zs. Sándor A		· · · · · · · · · · · · · · · · · · ·					

CONFIDENTIAL - Reproduction, publication and dissemination of this publication, enclosures hereto and the information contained therein is prohibited without MAGNETEC's prior written consent. Disclosing the specification to third parties or using its content without written permission from MAGNETEC is strictly forbidden and every offender is liable to pay the corresponding damages.