



Product specification for inductive components

Form: MF04.05 (F108)
Revision: 01

Client:	MAGNETEC GmbH	Magnetec P/N:	M-361	Magnetec A/N:	12351
Client's P/N:	/	PS Index:	04	PS Revision:	03
Subject:	CT Wandler				

1. Mechanical Outline

Nominal equivalent round core:

25 x 20,1 x 6,0


Finished product dimensions:

OD \leq **26,5**

ID \geq **18,8**

H \leq **7,8**

[dimensions] = mm



2. Core data (nominal values)

Core material:	NANOPERM®	$L_{Fe} = 7,06 \text{ cm}$	$A_{Fe} = 0,11 \text{ cm}^2$
Permeability level:	1.600	@ frequency 1 kHz	@ H peak 25 mA/cm

3. Inspection values (at room temperature, unless otherwise stated)

Measured value	Measurement limits	Frequency	$I_{eff} \times N$ [mA x turn]
AI [nH]	294 - 333	1 kHz	125

4. Core finishing

Type:	Cased
Marking:	MAGNETEC M-361-04 YM (YM = Production year/month)
Packaging:	63 pcs. per layer; 9 layers per carton box; PU = 567 pcs.

5. Comments

5 % measurement deviation has to be considered,

Visit http://www.magnetec.de/fileadmin/pdf/pb_ds.pdf for further information.

Index / Revision	Alteration	Date
03 / 01	Product Specification	13.03.2006
04 / 02	AL measurement	17.04.2007
04 / 03	Add one sentence to the comments	22.01.2019

Created:	Z. Braxátor 22.01.2019	Approved (Techn):	F. Záborszky 12.02.2019	Approved (Quality):	R. Montvai 12.02.2019	Released:	P. Seiz 15.03.2019
-----------------	---------------------------	--------------------------	----------------------------	----------------------------	--------------------------	------------------	-----------------------

Disclosing the specification to third parties or using its content without written permission from MAGNETEC is strictly forbidden and every offender is liable to pay the corresponding damages