


Product specification for inductive components

Form: Revision: MF04.05 (F108)

CONFIDENTIAL - Reproduction, publication and dissemination of this publication, enclosures hereto and the information contained therein is prohibited without MAGNETEC 's prior written consent.

Client:	MAGNETEC	Magnetec P/N:	M-667		
Client's P/N:	/	PS Index:	01	PS Revision:	02
Subject:	EMC Wandler				



2. Core data (nominal values)					
Core material:	NANOPERM®	L _{Fe} = 57,96 cm	$A_{Fe} = 2,72 \text{ cm}^2$		
Permeability level:		@ frequency	@ H peak		
	1.000	10 and 100 kHz	3 mA/cm		

3. Inspection values (at room temperature, unless otherwise stated)					
Measured value	Measurement limits	Frequency	leff x N [mA x turn]		
AL [µH]	0,41 - 0,82	10 and 100 kHz	123,0		

AL [μH]		0,41 - 0,82	10 and 100 kHz 123,0
4. Core finishing			
Туре:	Cased		

Marking: MAGNETEC M-667-01 YM (YM = Year/Month), acc. to IEC 62 5.1

Packaging: Pu = 2 pcs.

5. Comments
Visit http://www.magnetec.de/fileadmin/pdf/pb ds.pdf for further information.

Index / Revision	Alteration	Date
01 / 01	Product Specification	29.03.2012
01 / 02	Finished product dimension change	05.10.2012

Created:	Z. Palánki	Approved	F. Zámborszky	Approved	J. Gulyás	Released:	F. Rauscher
	05.10.2012	(Techn):	08.10.2012	(Quality):	09.10.2012		09.10.2012

CONFIDENTIAL - Reproduction, publication and dissemination of this publication, enclosures hereto and the information contained therein is prohibited without MAGNETEC's prior written consent. Disclosing the specification to third parties or using its content without written permission from MAGNETEC is strictly forbidden and every offender is liable to pay the corresponding damages .