

Product specification for inductive components

CONFIDENTIAL - Reproduction, publication and dissemination of this publication, enclosures hereto and the information contained therein is prohibited without MAGNETEC 's prior written consent.

Client:	MAGNETEC	Magnetec P/N:	M-1630		
Client's P/N:	/	PS Index:	01	PS Revision:	01
Subject:	EMC Wandler				

•							
1. Mechanical Outline							
Nominal equivalent round core: 160 x 130 x (30x6) Finished product dimensions: $OD \leq$ $ID \geq$ $H \leq$ [dimensions] = mm $OD1 = 207\pm0,5$ $ID1 = 155\pm2$ $OD2 = 137,5\pm0,5$ $ID2 = 69\pm1$ $F = 284\pm5$ $H = 309\pm5$		2 - E Marking					
2 Core data (persingly clube)							
2. Core data (nominal values)							
Core material: NANOPERM® $L_{Fe} = 44,7 \text{ cm}$ $A_{Fe} = 19,8 \text{ cm}^2$							
Permeability level :	@ frequency @ H peak						
3. Inspection values (at room	temperature, unless otherwise stated)						
Measured value	Measurement limits		x N [mA x turn]				
AL [µH]	125,4 - 270	10 kHz	100				
AL [µH]	75,6 - NA	100 kHz	100				
5. Comments LASER MARKING ON HOLDE Data matrix MAGNETEC M -163 Data matrix with the following cor (P=Plant code of MH YYWW= Yet	yer; 1 layers per carton box; PU = 1 pcs. R : D-01						
Index / Revision Alteration							
01/01 Product Spe	cification	15.09.2022					
Created: P. Kárpáti A	pproved Z. Makovinyi Approved D	D. Parragi Released :	B. Kessler				

CONFIDENTIAL - Reproduction, publication and dissemination of this publication, enclosures hereto and the information contained therein is prohibited without MAGNETEC's prior written consent. Disclosing the specification to third parties or using its content without written permission from MAGNETEC is strictly forbidden and every offender is liable to pay the corresponding damages .