

FORM Identifier: F 108 Revision: 04 Page: 1/1	Product specification for inductive components	MAGNETEC GmbH Industriestrasse 7 D-63505 Langenselbold
---	--	---



Client:	MAGNETEC	Magnetec P/N:	M-1207	Magnetec A/N:	12772
Client's P/N:	/	PS Index:	01	PS Revision:	01
Subject:	EMC Wandler			Type:	

1. Mechanical Outline	
Nominal core dimensions: 30 x 20 x (10x10) Finished product dimensions: OD ≤ 36 ID ≥ 14,5 H ≤ 135 [dimensions] = mm	

2. Core data (nominal values)			
Core material:	NANOPERM®	$L_{Fe} = 7,75 \text{ cm}$	$A_{Fe} = 3,75 \text{ cm}^2$
Permeability level:	8 000	@ frequency 10 kHz	@ H peak 3 mA/cm

3. Inspection values				
	Measured value	Measurement limits	Frequency	leff x N [mA x turn]
	AL [μH]	34 - 68	10 kHz	16,5
	AL [μH]	29 - NA	100 kHz	16,5

4. Core finishing	
Type:	Cased
Marking:	see below
Packaging:	5 pcs. per layer; 2 layers per carton box ; PU = 10 pcs.

5. Comments :	
	Marking: CoolTUBE MAGNETEC M-1207-01 YM YM = Year/Month acc. to IEC 60062 6.1.1

Index / Revision	Alteration	Date
01 / 01	First issue	26.01.2016

Created:	Z. Palánki	Approved (Techn):	F. Záborszky	Approved (Quality):	J. Gulyás	Released:	T. Trupp
	26.01.2016		03.02.2016		03.02.2016		03.02.2016