

FORM Identifier: F 108 Revision: 03 Page: 1/1	Product specification for inductive components	MAGNETEC GmbH Industriestrasse 7 D-63505 Langenselbold
---	---	---



Client:	MAGNETEC	Magnetec P/N:	M-389	Magnetec A/N:	12357
Client's P/N:	/	PS Index:	02	PS Revision:	02
Subject:	CT WANDLER			Type:	

1. Mechanical Outline	
Nominal core dimensions: 19,1 x 15,2 x 6,0 Finished product dimensions: OD ≤ 20,5 ID ≥ 13,8 H ≤ 7,8 [dimensions] = mm	

2. Core data			
Core material:	NANOPERM®	$L_{Fe} = 5,37 \text{ cm}$	$A_{Fe} = 0,09 \text{ cm}^2$
Nominal values:	Permeability level	@ frequency	@ H_{max}
	3.400	1 kHz	25 mA/cm

3. Inspection values				
	Measured value	Measurement limits	Frequency	$I_{eff} \times N$ [mA x turn]
	AL [nH]	658 - 740	1 kHz	95

4. Core finishing	
Type:	Cased
Marking:	MAGNETEC - M-389-02 YM" (YM = Production year/month)
Packaging:	75 pcs. per layer; 9 layers per carton box; PU = 675 pcs.

5. Comments:	
	<input checked="" type="checkbox"/> Date code (YM) on marking acc. to IEC 62 5.1; YM = production year and month <input checked="" type="checkbox"/> RoHS compliant acc. to Directive 2002/95/EC

Index / Revision	Alteration	Date
01 / 01	Product specification	15.06.2006
02 / 02	AL measurement	18.01.2007

Created:	Zs. Sándor	Approved (Techn):	F. Zámorszky	Approved (Quality):	V. Kaposztas	Released:	F. Rauscher
	18.01.2007		08.02.2007		08.02.2007		08.02.2007