

FORM Identifier: F 108 Revision: 03 Page: 1/1	Product specification for inductive components	MAGNETEC GmbH Industriestrasse 7 D-63505 Langenselbold
---	---	---



Client:	MAGNETEC GmbH	Magnetec P/N:	M-484	Magnetec A/N:	82059
Client's P/N:	/	PS Index:	01S	PS Revision:	01
Subject:	EMC Wandler			Type:	E

1. Mechanical Outline	
Nominal core dimensions: 50 x 40 x 25 Finished product dimensions: OD ≤ 53,6 ID ≥ 35,9 H ≤ 29,5 [dimensions] = mm DEVELOPMENT SAMPLE	

2. Core data			
Core material:	NANOPERM®	$L_{Fe} = 14,08 \text{ cm}$	$A_{Fe} = 0,91 \text{ cm}^2$
Nominal values:	Permeability level	@ frequency	@ H peak
	55.000	10 kHz	3,01 mA/cm

3. Inspection values				
	Measured value	Measurement limits	Frequency	$l_{eff} \times N$ [mA x turn]
	AL [μH]	34,4 - 68,7	10 kHz	30,0

4. Core finishing	
Type:	Cased
Marking:	MAGNETEC M-484-01 YM SAQMPLE
Packaging:	10 pcs. per layer; 4 layers per carton box; PU = 40 pcs.

5. Comments:	
	<input checked="" type="checkbox"/> Marking date code (YM) acc. to IEC 62 5.1; YM = production year and month <input checked="" type="checkbox"/> RoHS compliant according to directive 2002/95/EC

Index / Revision	Alteration	Date
01S/ 01	Sample Specification	10.03.2007

Created:	Á. Kovách	Approved (Techn):		Approved (Quality):		Released:	
	10.03.2007						