

FORM F 108  
Revision: 05  
Page: 1/1

Product specification  
for inductive components

MAGNETEC GmbH  
Industriestrasse 7  
D-63505 Langenselbold

Client:	MAGNETEC	Magnetec P/N:	M-672	Magnetec A/N:	12615
Client's P/N:	/	PS Index:	01	PS Revision:	03
Subject:	EMC Wandler				

1. Mechanical Outline

Nominal equivalent round core:

63 x 50 x 30


Finished product dimensions:

OD  $\leq$  69,5

ID  $\geq$  43,0

H  $\leq$  36,0

[dimensions] = mm



2. Core data (nominal values)

Core material:	NANOPERM®	$L_{Fe} = 17,40 \text{ cm}$	$A_{Fe} = 1,60 \text{ cm}^2$
Permeability level:	2.000	@ frequency 10 and 100 kHz	@ H peak 3 mA/cm

3. Inspection values (at room temperature, unless otherwise stated)

Measured value	Measurement limits	Frequency	leff x N [mA x turn]
AL [ $\mu$ H]	1,62 - 3,23	10 and 100 kHz	37,0

4. Core finishing

Type:	Cased
Marking:	MAGNETEC M-672-01 YM (YM = Year/Month), acc. to IEC 62 5.1
Packaging:	8 pcs. per layer; 2 layers per carton box; PU = 16 pcs.

5. Comments

Visit [http://www.magnetec.de/fileadmin/pdf/pb\\_ds.pdf](http://www.magnetec.de/fileadmin/pdf/pb_ds.pdf) for further information.

Index / Revision	Alteration	Date
01 / 01	Product Specification	27.03.2012
01 / 02	Finished dimensions corrected	18.06.2012
01 / 03	Harmonization of part and finished product dimensions	17.01.2020

Created:	Z. Braxátor 17.01.2020	Approved (Techn):	F. Záborszky 17.01.2020	Approved (Quality):	G. Zsák 17.01.2020	Released:	B. Kessler 17.01.2020
----------	---------------------------	-------------------	----------------------------	---------------------	-----------------------	-----------	--------------------------

Disclosing the specification to third parties or using its content without written permission from MAGNETEC is strictly forbidden and every offender is liable to pay the corresponding damages