

<b>FORM</b> Identifier: F 108 Revision: 04 Page: 1/1	<b>Product specification          for inductive components</b>	<b>MAGNETEC GmbH</b> Industriestrasse 7 D-63505 Langenselbold
---	--	---



<b>Client:</b>	<b>MAGNETEC</b>	<b>Magnetec P/N:</b>	<b>M-986</b>	<b>Magnetec A/N:</b>	<b>12765</b>
<b>Client's P/N:</b>	/	<b>PS Index:</b>	<b>01</b>	<b>PS Revision:</b>	<b>01</b>
<b>Subject:</b>	<b>EMC Wandler</b>			<b>Type:</b>	

1. Mechanical Outline	
Nominal core dimensions: <b>160 x 130 x 30</b>  Finished product dimensions: OD $\leq$ <b>198 (OD1) / 112,5 (OD2)</b> ID $\geq$ <b>154,5 (ID1) / 69 (ID2)</b> H $\leq$ <b>36</b>  [dimensions] = mm	

2. Core data (nominal values)			
Core material:	<b>NANOPERM®</b>	$L_{Fe} = 45 \text{ cm}$	$A_{Fe} = 3,57 \text{ cm}^2$
Permeability level:	<b>4 000</b>	@ frequency <b>10 kHz</b>	@ H peak <b>3 mA/cm</b>

3. Inspection values				
	Measured value	Measurement limits	Frequency	leff x N [mA x turn]
	<b>AL [μH]</b>	<b>2,8 - 5,6</b>	<b>10 kHz</b>	<b>96</b>
	<b>AL [μH]</b>	<b>2,8 - NA</b>	<b>100 kHz</b>	<b>96</b>

4. Core finishing	
Type:	<b>Cased</b>
Marking:	<b>MAGNETEC M-986-01 YM (YM = Year/Month), acc. to IEC 60062 6.1.1</b>
Packaging:	<b>1 pcs. per layer; 5 layers per carton box ; PU = 5 pcs.</b>

5. Comments :	

Index / Revision	Alteration	Date
01 / 01	First issue	16.11.2015

<b>Created:</b>	Z. Palánki	<b>Approved (Techn):</b>	F. Zámorszky	<b>Approved (Quality):</b>	J. Gulyás	<b>Released:</b>	T. Trupp
	16.11.2015		01.12.2015		01.12.2015		01.12.2015