

FORM Identifier: F 190 Revision: 02 Page: 1/1	Product specification for Inductive Components	MAGNETEC GmbH Industriestrasse 7 D-63505 Langenselbold
---	--	---

Client:	MAGNETEC	Magnetec P/N:	MB-607	Magnetec A/N:	12722
Client's p/n:	/	PS Index:	02	PS Revision:	01
Subject:	EMC Component			Type:	

1.1 Mechanical outline	Wiring diagram

2. Nominal values			
Core material:	NANOPERM®	Wire Resistance:	<= 6 mOhms
Nominal voltage:	250 Veff AC	High voltage strength:	Up,eff = 2,5 kV
Nominal inductance:	2 x 6,3 mH	Operating temperature:	-40 ... +70 °C
Nominal current:	16 A	Storage temperature::	-40 ... +85 °C
Leakage inductances:	ca. 5 µH	Design standard:	EN 60938-1
No. of turns:	N1 = N2 = 10	Wire diameter:	2x 1,12 mm
Comments:			

3. Inspection values			
	Measured value	Measuring limits	Measuring configurations
	Inductivity L 1; L2 [mH]	4,0 - 8,9	f = 10 kHz Ueff = 0,1 V
	Inductivity L 1; L2 [mH]	1,3 - NA	f = 100 kHz Ueff = 0,1 V
	Wire resistance Rcu 1; Rcu2 [mOhms]	0 - 6,0	T = 23±3°C
	HV strength between N 1; N2 / liso<1mA	OK - NOK	Ueff = 2,5 kV t = 2 s
		-	

4. Others	
	Marking: MAGNETEC MB -607-02 YM (YM = Year/Month), acc. to IEC 60062 6.1.1 Packaging: 30 pcs. per layer, 4 layers per carton box ; PU = 120 pcs. Comments:

Index / Rev.	Alteration	Date
02 / 01	First issue	13.04.2015

Created:	Z. Palánki	Approved (Techn):	F. Zámorszky	Approved (Quality):	J. Gulyás	Released:	T. Trupp
	13.04.2015		28.04.2015		28.04.2015		28.04.2015