

FORM Identifier: F 190 Revision: 02 Page: 1/1	<b>Product specification for Inductive Components</b>	<b>MAGNETEC GmbH</b> Industriestrasse 7 D-63505 Langenselbold
--	---	---

Client:	<b>MAGNETEC</b>	Magnetec P/N:	<b>MB-694</b>	Magnetec A/N:	<b>12750</b>
Client's p/n:	/	PS Index:	<b>01</b>	PS Revision:	<b>02</b>
Subject:	<b>EMC Component</b>			Type:	

<b>1.1 Mechanical outline</b>	<b>Wiring diagram</b>

2. Nominal values			
Core material:	<b>NANOPERM®</b>	Wire Resistance:	<b>&lt;= 40 mOhms</b>
Nominal voltage:	<b>250 Veff AC</b>	High voltage strength:	<b>Up,eff = 2,5 kV</b>
Nominal inductance:	<b>2 x 11 mH</b>	Operating temperature:	<b>-40 ... +70 °C</b>
Nominal current:	<b>3 A</b>	Storage temperature:	<b>-40 ... +85 °C</b>
Leakage inductances:	<b>ca. 10 µH</b>	Design standard:	<b>EN 60938-1</b>
No. of turns:	<b>N1 = N2 = 17</b>	Wire diameter:	<b>0,56 mm</b>
Comments:			

3. Inspection values			
	Measured value	Measuring limits	Measuring configurations
	Inductivity L 1; L2 [mH]	7,0 - 15,6	f = 10 kHz Ueff = 0,1 V
	Inductivity L 1; L2 [mH]	2,15 - NA	f = 100 kHz Ueff = 0,1 V
	Wire resistance Rcu 1; Rcu2 [mOhms]	0 - 40	T = 23±3°C
	HV strength between N 1; N2 / Iiso < 1mA	OK - NOK	Ueff = 2,5 kV t = 2 s
		-	

4. Others	
Marking:	<b>MAGNETEC MB-694-01 YM (YM = Year/Month), acc. to IEC 60062 6.1.1</b>
Packaging:	<b>60 pcs. per layer, 6 layers per carton box ; PU = 360 pcs.</b>
Comments:	

Index / Rev.	Alteration	Date
01 / 01	First issue	09.07.2015
01 / 02	Drawing change	26.11.2015

Created:	Z. Palánki	Approved (Techn):	F. Zámbořszky	Approved (Quality):	J. Gulyás	Released:	T. Trupp
	26.11.2015		01.12.2015		01.12.2015		01.12.2015